



Herramienta soldadura de alimentación AM120

Proporciona una solución perfecta para la reelaboración rápida y precisa de SMD de componentes de chips y SOP pequeños/medianos de ensamblajes de PCB.

El sistema de ajuste garantiza que los cartuchos estén igualmente alineados, con simetría vertical y rotatoria.

Las micro pinzas ajustables AM120 se pueden usar con las unidades de control DIU, DDU y DMU mediante el soporte AMS y también pueden funcionar con la estación de micro pinzas CDP.

Requiere cartuchos de la gama C120.



Ficha Técnica


| JBC-AM120-A | Descripción |
|--------------------|-------------------|
| Longitud del cable | 1,5 metros |
| Dimensiones | 277 x 73 x 50 mm. |
| Peso | 0,102 kg. |

Gama de cartuchos C120

| | Ref. | Description | Image and dimensions | Suggested components | Compatible with |
|--|----------------|--------------------------------------------------|----------------------|-----------------------------------------------------|-----------------------------------------------------------|
| | C120001 | Conical Bent Cartridge Ø 0.2 mm Ø 0.008 in | | Package 0201, 0402 | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| | C120002 | Conical Bent Cartridge Ø 0.2 mm Ø 0.008 in | | Package 0201, 0402 | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| | C120902 | Conical Bent Cartridge Ø 0.3 mm Ø 0.012 in | | Package 0201, 0402 Fine pitch 0.65 mm QFP, IC | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| | C120006 | Conical Bent Cartridge Ø 0.5 mm Ø 0.020 in | | Package 0603 QFP, IC | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |



| Ref. | Description | Image and dimensions | Suggested components | Compatible with |
|----------------|-----------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------|
| C120004 | Conical Bent Cartridge Ø 0.7 mm S1 Ø 0.028 in | | SMD capacitors QFP, IC Through-hole | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120012 | Conical Bent Cartridge Ø 0.7 mm S2 Ø 0.028 in | | SMD capacitors QFP, IC Through-hole Tip with an extra tinned surface | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| | C120011 Chisel Bent Cartridge 0.6 x 0.3 mm 0.024 x 0.012 in | | Package 0603 | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| | C120013 Blade Cartridge 2 mm 0.079 in | | LED SMD 2727, 1921, 1415 | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120003 | Blade Cartridge 3 mm 0.118 in | | Package 1210, 1812 SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120007 | Blade Cartridge 3.5 mm Right 0.138 in | | Package 1210, 1812 SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |



| Ref. | Description | Image and dimensions | Suggested components | Compatible with |
|----------------|--------------------------------------------|--------------------------------------------------------------------------------|-------------------------------|-----------------------------------------------------------|
| C120008 | Blade Cartridge 3.5 mm Left 0.138 in | <p>C120007 C120008</p> <p>mm (in)</p> | Package 1210, 1812 SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120005 | Blade Cartridge 5 mm 0.197 in | <p>0.7 (0.028) 5 (0.197)</p> <p>mm (in)</p> | SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120009 | Blade Cartridge 6 mm Right 0.236 in | <p>0.7 (0.028) 6 (0.236)</p> <p>C120010 C120009</p> <p>mm (in)</p> | SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |
| C120010 | Blade Cartridge 6 mm Left 0.236 in | <p>0.7 (0.028) 6 (0.236)</p> <p>C120010 C120009</p> <p>mm (in)</p> | SO, SOT | Stations: CDP, DIU, DDU, DMU Tools: AM120, PA120 |