

Estación de soldadura de precisión CDS

Esta estación es ideal cuando se trabaja en PCB pobladas o bajo una lupa.

Utiliza el soldador de precisión T210, la herramienta de soldadura perfecta para trabajos de precisión con requisitos de potencia media. El soldador T210 funciona con la gama de cartuchos C210.

Proporciona la mejor calidad de soldadura gracias al sistema de soldadura más eficiente de JBC y, además, los modos de suspensión e hibernación ayudan a prolongar la vida útil de las puntas.

Esta estación incluye:

- Configuración rápida y sencilla de la estación gracias al teclado de 7 teclas.
- Portacartuchos para almacenar hasta cuatro cartuchos, así como Extractor de Cartuchos y Colector de Cables.
- Conectividad a Extractor de Humos JBC (conector RJ12).



Vídeos



Más vídeos en nuestro canal de YouTube

JBC-CD-2SQQ	Descripción
Temperatura seleccionable	90 a 450 °C
Conectividad USB-B	Software PC/Actualización de firmware
Compensación de potencial	Conexión opcional a EPA
Fusible de puesta a tierra	F 1.25A
Voltaje	230 V
Pico de sobretensión	40 W – 23.5 V
Temperatura de funcionamiento	10 a 50 °C
Dimensiones	170 x 176 x 145 mm.
Peso	2.70 kg.
Dimensión del paquete	234 x 231 x 258 mm.
Peso del paquete	3.27 kg.



Soldador de precisión T210

El soldador de precisión T210 es perfecto para trabajos de soldadura de precisión con requisitos de potencia media. Por su tamaño, es capaz de trabajar SMD convencionales o pequeños incluso bajo una lupa.

Su tip-to-grip ergonómico y de corta distancia garantiza una mayor precisión y comodidad.

Puede funcionar con unidades de control DIU , DDU y DMU utilizando el soporte ADS y, además, con estaciones de soldadura CDS, CDB, CDES y CDEB.





El soldador de precisión T210 funciona con la gama de cartuchos C210.




Ficha Técnica


JBC-T210-A	Descripción
Longitud del cable	1,5 metros
Dimensiones	123 x 14 x 14 mm.
Peso	0,06 kg.
Dimensiones del paquete	235 x 40 x 40 mm.
Peso del paquete	0,11 kg.








Gama de cartuchos C210

	Ref.	Description	Image and dimensions	Suggested components	Compatible with
	C210020	Conical Cartridge Ø 0.1 mm Ø 0.004 in		Package 01005, 0201 Very fine pitch 0.4 mm QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
	C210009	Conical Cartridge Ø 0.2 mm Ø 0.008 in		Package 01005, 0201 Very fine pitch 0.4mm QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
	C210016	Conical Cartridge Ø 0.3 mm S1 Ø 0.012 in		Package 0201, 0402 Fine pitch 0.65 mm QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N



Ref.	Description	Image and dimensions	Suggested components	Compatible with
C210001	Conical Cartridge Ø 0.3 mm S2 Ø 0.012 in		Package 0201, 0402 Fine pitch 0.65 mm QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210013	Conical Cartridge Ø 0.5 mm Ø 0.020 in		Package 0603 QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210003	Conical Cartridge Ø 0.6 mm Ø 0.024 in		General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210005	Conical Cartridge Ø 1 mm Ø 0.039 in		General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
	C210002 Conical Bent Cartridge Ø 0.2 mm Ø 0.008 in		Package 0201, 0402	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210010	Conical Bent Cartridge Ø 0.3 mm Ø 0.012 in		Package 0201, 0402 Fine pitch 0.65 mm QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N



Ref.	Description	Image and dimensions	Suggested components	Compatible with
C210014	Conical Bent Cartridge Ø 0.5 mm Ø 0.020 in		Package 0603 QFP, IC	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210004	Conical Bent Cartridge Ø 0.7 mm Ø 0.028 in		General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
	C210036 Bevel Cartridge Ø 0.6 mm Ø 0.024 in		Drag Soldering General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210006	Bevel Cartridge Ø 1 mm Ø 0.039 in		Drag Soldering General use	Stations: CD, CDE, DIU, DDU, DMU Tools: T210, T210P, T210N
C210027	Bevel Cartridge Ø 1.5 mm Ø 0.059 in		Drag Soldering General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N
C210031	Bevel Cartridge Ø 2 mm Ø 0.079 in		Drag Soldering General use	Stations: CDS, CDES, DIU, DDU, DMU Tools: T210, T210P, T210N