

PRODUCT

DATASHEET

UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018



C-VL1111S

Clean-Room Professional C-VL1111S

DIMENSIONS

PRODUCI		DIIVIENSIONS	C-AF11112		
		Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	440 mm 470 mm 480 mm 530-590 mm 60 mm 430 mm 420-550 mm		
TECHNICAL DE	SCRIPTION				
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.				
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.				
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.				
	VALENCIA Composition: outside 100% PVC, inside 100% polyester Hi-Loft2 TM Weight: 650 g/m² Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Colour fastness to light: DIN 54004 (Level 6) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1), NF P 92-503 (M2) Colours: Throna colour chart				
Markanian	Colour fastness to light Flammability: DIN EN 1 Colours: Black 014 Resistant to disinfectar	470-2 (> 100.000 Martindale cycles) : DIN EN ISO 105-B02 (Level 6) 021-1+2, BS 5852-0+1Crib 5, MVSS302 nts, blood and urine			
Mechanism	PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.				
Lift action Base	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. 0901C : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.				
Castors	0302: hard castors (Ø 5	0 mm) in black nylon, self-braking.			
ACCESSORIES					
0860N M-0311	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors.				
M-0351	Glides in black nylon (h	55 mm / $\not 0$ 50 mm). Instead of castors.			
TEST					

Rev. 0	01-06-2017	Clean-Room Professional: C-VL1111S	Page 1 of 1
Rev. 1	01-01-2020	Clean-Room Professional: C-VL1111S	Page 1 of 1



SCHEDA TECNICA

UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

UNI EN 1335-1+2+3

D. Lgs. 81/2008 type B

