

DATASHEET

UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018



Clean-Room Professional SI-VCBRMCP2

Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Backrest Internal structure in recyclable techno-polymer for internal components protection. Padding Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC. Upholstery VALENCIA Composition: outside 100% PVC, inside 100% polyester Hi-Loft2 TM Weight: 650 g/m² Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Colour fastness to light: DIN 54004 (Level 6) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1 NF P 92-503 (M2) Colours: Throna colour chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 740 g/m² Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Colour fastness to light: DIN EN ISO 105-B02 (Level 6) Flammability: DIN EN 1021-1+2, B5 5852-0+1Crib 5, MVSS302 Colours: Black 014 Resistant to disinfectants, blood and urine PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3. Lift action Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. Base 0901c: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.	PRODUCT		DIMENSIONS	C-VL1011S			
Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Backrest			Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width	470 mm 480 mm 420-480 mm 60 mm 430 mm			
Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection. Backrest	TECHNICAL DI	ESCRIPTION					
Backrest Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection. Padding Seat in PU-Flex, 40 mm thickness and 40 g/L density.	Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1.					
Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC. VALENCIA Composition: outside 100% PVC, inside 100% polyester Hi-Loft2 TM Weight: 650 g/m² Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Colour fastness to light: DIN 54004 (Level 6) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1 NF P 92-503 (M2) Colours: Throna colour chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 740 g/m² Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Colour fastness to light: DIN EN ISO 105-B02 (Level 6) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MIVSS302 Colours: Black 014 Resistant to disinfectants, blood and urine PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3. Lift action Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. Base 0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. Castors 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.	Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs.					
Composition: outside 100% PVC, inside 100% polyester Hi-Loft2 TM Weight: 650 g/m² Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Colour fastness to light: DIN 54004 (Level 6) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1 NF P 92-503 (M2) Colours: Throna colour chart TOLEDO Composition: 84% PVC, 16% polyester Weight: 740 g/m² Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Colour fastness to light: DIN EN ISO 105-802 (Level 6) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Colours: Black 014 Resistant to disinfectants, blood and urine Mechanism PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3. Lift action Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. Base 0901c: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. Castors 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.	Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density.					
Composition: 84% PVC, 16% polyester Weight: 740 g/m² Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Colour fastness to light: DIN EN ISO 105-B02 (Level 6) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Colours: Black 014 Resistant to disinfectants, blood and urine Mechanism PC: PERMANENT CONTACT, backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3. Lift action Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. Base 0901c: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. Castors 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.	Opnoistery	Composition: outside 100% PVC, inside 100% polyester Hi-Loft2 [™] Weight: 650 g/m² Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Colour fastness to light: DIN 54004 (Level 6) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1), NF P 92-503 (M2) Colours: Throna colour chart					
adjustment. According to UNI EN 1335-3. Lift action Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550. Base 0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. Castors 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		Composition: 84% PVC, 16% polyester Weight: 740 g/m² Abrasion: DIN EN ISO 5470-2 (> 100.000 Martindale cycles) Colour fastness to light: DIN EN ISO 105-B02 (Level 6) Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302 Colours: Black 014					
Base 0901C: 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3. Castors 0302: hard castors (Ø 50 mm) in black nylon, self-braking. ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.	Mechanism	· ·					
ACCESSORIES 0860N Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.		0901C : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.					
 Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish. M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors. 	Castors	0302: hard castors (Ø 50	mm) in black nylon, self-braking.				
M-0311 Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302 castors. M-0351 Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.	ACCESSORIES						
		Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of 0302					
TEST	M-0351	Glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.					
	TEST						

Rev. 0	01-06-2017	Clean-Room Professional: C-VL1011S	Page 1 of 1
Rev. 1	01-01-2020	Clean-Room Professional: C-VL1011S	Page 1 of 1



SCHEDA TECNICA

UNI EN ISO 9001:2015 UNI EN ISO 14001:2015 UNI ISO 45001:2018

UNI EN 1335-1+2+3

D. Lgs. 81/2008 type B

