


## Clean-Room Professional SI-VCMRMCP2 / SI-VCARMCP2

PRODUCT	DIMENSIONS	C-VL1461HS	C-VL1471HS
	Seat depth from lumbar support	440 mm	440 mm
	Seat depth	470 mm	470 mm
	Seat width	480 mm	480 mm
	Backrest height from seat	420-480 mm	420-480 mm
	Backrest height adjustment	60 mm	60 mm
	Backrest width	430 mm	430 mm
	Seat height	500-700 mm	600-850 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in recyclable techno-polymer for internal components protection.
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.

Upholstery	<p><b>VALENCIA</b>            Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™            Weight: 650 g/m<sup>2</sup>            Abrasion: DIN EN ISO 12947-2 (&gt; 300.000 Martindale cycles)            Colour fastness to light: DIN 54004 (Level 6)            Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1), NF P 92-503 (M2)            Colours: Throna colour chart</p> <p><b>TOLEDO</b>            Composition: 84% PVC, 16% polyester            Weight: 740 g/m<sup>2</sup>            Abrasion: DIN EN ISO 5470-2 (&gt; 100.000 Martindale cycles)            Colour fastness to light: DIN EN ISO 105-B02 (Level 6)            Flammability: DIN EN 1021-1+2, BS 5852-0+1Crib 5, MVSS302            Colours: Black 014            Resistant to disinfectants, blood and urine</p>
------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Mechanism	<b>PC: PERMANENT CONTACT</b> , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0901C</b> : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.
Glides	<b>0351</b> : glides in black nylon (h 55 mm / Ø 50 mm).

### ACCESSORIES

0860N	Height adjustable armrests. Supporting structure in steel with top in nylon. Black finish.
M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors (Ø 50 mm) in black nylon, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.

### TEST

Rev. 0	01-06-2017	Clean-Room Professional: C-VL1461HS / C-VL1471HS	Page 1 of 1
Rev. 1	01-01-2020	Clean-Room Professional: C-VL1461HS / C-VL1471HS	Page 1 of 1

UNI EN 1335-1+2+3

D. Lgs. 81/2008 type B