


ESD Standard A-VL1011AS

PRODUCT		DIMENSIONS	A-VL1011AS
		Seat depth from lumbar support	440 mm
		Seat depth	470 mm
		Seat width	480 mm
		Backrest height from seat	420-480 mm
		Backrest height adjustment	60 mm
		Backrest width	430 mm
		Seat height	420-550 mm
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 11 mm variable thickness. Low formaldehyde emission according to class E1. Outer shell in recyclable techno-polymer for internal components protection.		
Backrest	Internal structure in recyclable techno-polymer anatomically shaped with integrated reinforcement ribs. Outer shell in conductive recyclable techno-polymer for internal components protection.		
Padding	Seat in PU-Flex, 40 mm thickness and 40 g/L density. Backrest in PU-Flex, 35 mm thickness and 40 g/L density. Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	ESD2 Composition: 99% polypropylene, 1% carbon Weight: 230 g/m ² Abrasion: UNI EN ISO 12947 (>30.000 Martindale cycles) Pilling: ISO 12945-2 (4-5) Colour fastness to rubbing: EN ISO 105-X12 (Dry/Wet 4-5) Colour fastness to light: EN ISO 105-B02 Xenotest (Level 5) Flammability: IT - Class 1, EN 1021-1+2, BS 5852 Crib 5, California TB 117 Colours: Anthracite 1601 / Black 1654		
Mechanism	PC: PERMANENT CONTACT , backrest inclination of 20° lockable in all positions. Knob activated backrest height adjustment. According to UNI EN 1335-3.		
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), chrome finish. Class 4 according to DIN 4550.		
Base	0901C : 5-star base (Ø 700 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish. According to ANSI/BIFMA X5.1, BS 5459 A.5.1-A.5.5 and UNI EN 1335-3.		
Castors	0321 : conductive castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking.		
ACCESSORIES			
M-0331	Conductive glides in black nylon (h 32 mm / Ø 50 mm). Instead of castors.		
TEST			
UNI EN 1335-1+2+3			
EN 100015-1			
IEC 61340-5-1			
D. Lgs. 81/2008 type B			