


## Production PU SI-WMCRCP/ SI-WASRCP

PRODUCT	DIMENSIONS	P-WG1860HP	P-WG1870HP
	Seat depth from lumbar support	380 mm	380 mm
	Seat depth	390 mm	390 mm
	Seat width	390 mm	390 mm
	Backrest height from seat	340-410 mm	340-410 mm
	Backrest height adjustment	70 mm	70 mm
	Backrest width	430 mm	430 mm
	Seat height	480-680 mm	580-830 mm

### TECHNICAL DESCRIPTION

Seat	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC.
Backrest	Internal structure in steel rods ( $\varnothing$ 10 mm), covered by a compound of ultra-light integral polyurethane (PU-Touch). Colour Anthracite GRY. Non-toxic material and without CFC/HCFC. Outer shell in shaped metal, painted in black.
Mechanism	<b>GS:</b> GAS LIFT, seat height adjustable. Knob activated backrest height adjustment.
Lift action	Central piston ( $\varnothing$ 28 mm) protected by steel tube ( $\varnothing$ 50 mm), black finish. Class 4 according to DIN 4550.
Base	<b>0902P:</b> 5-star base ( $\varnothing$ 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	<b>0351:</b> glides in black nylon (h 55 mm / $\varnothing$ 50 mm).

### ACCESSORIES

M-0311	Soft castors ( $\varnothing$ 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
M-0302	Hard castors ( $\varnothing$ 50 mm) in black nylon, self-braking. Instead of glides.
M-0902C	5-star base ( $\varnothing$ 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.
M-0903COL	5-star base ( $\varnothing$ 700 mm) in die-cast aluminum with internal reinforcement ribs. Varnished with RAL color on demand
M-0901V	5-star raised base ( $\varnothing$ 500 mm) in grey epoxy painted steel with rubber end-plugs.
0700	Circular footrest ( $\varnothing$ 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
0731	Circular footrest ( $\varnothing$ 600 mm), black steel ring, supports in black painted steel, two metal boards, height adjustable with a knob.

### TEST

PTP 177.0/20 Measurement of antibacterial activity on surfaces  
DIN 68877-1-2:2016