



Jewel™

- A. Insulating cap, ABS plastic.
- B. 300 series stainless steel backplate (0.406mm thick). Manufacturing date code is stamped into stainless steel backplate.
- C. Small cam lock, allows material replacement. 300 series stainless steel.

DESCRIPTION	4mm	10mm
Band, sapphire clasp	60000	60001
Band, ruby clasp	60002	60003
Band, amethyst clasp	60004	60020
Band, topaz clasp	60006	60007
Band, emerald clasp	60008	60009
Sapphire clasp only	60010	60011
Ruby clasp only	60012	60013
Topaz clasp only	60014	60015
Emerald clasp only	60016	60017
Amethyst clasp only	60018	60019
Elastic replacement strip	60005	

Circumference:
 Min: 63.5mm
 Max: 330mm
 Width: 22mm

- D. Large cam lock, allows size adjustment, maintains electrical continuity even when open. 300 series stainless steel.
- E. Floating cam lock* allows wide opening for easy adjustment and secures material down against base plate when closed.
- F. 4mm snap stud machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with .45Kg - 2.27Kg of perpendicular force. Durable, providing long life well beyond that of sheet metal snaps.
- G. Knit elastic band material of light blue fiber; 22mm wide and 2.5mm thick. 50 strands of textured polyester, 36 strands of lycra spandex and 14 strands of silver plated Nylon 6 yarn. Outer surface of light blue fibers act as an insulator.
- H. The conductive silver plated Nylon 6 (see G) represents 13.5% of the material by weight. The 14 strands of conductive Nylon 6 are randomly knit on the inner surface of the material and are electrically isolated from the outer surface (grey side).
- I. Underwriters Laboratory listing 90P1C.

Designed to satisfy wrist strap requirements of IEC 61340-5.

Jewel™ Lifetime Limited Warranty
 Charleswater Europe expressly warrants that Charleswater Europe Jewel™ Wrist Straps and Coil Cords will be free of defects in material (parts) and workmanship (labor). In addition, normal use will not cause Coil Cord resistor strain relief connection or Wrist Band 4 mm snap stud to wear sufficiently to open path-to-ground circuit. Within the lifetime warranty period, a credit for purchase of replacement Charleswater Europe Jewel™ products, or, at Charleswater Europe's option, the Charleswater Europe Jewel™ product will be repaired or replaced free of charge. If product credit is issued, the amount will be calculated based upon the original invoice purchase price.

Made in U.S.A.
 *U.S. Patent No. 4,662,695



JEWEL™ WRISTBAND, ELASTIC, ADJUSTABLE

CONDUCTIVE PRODUCTS LTD.
 UNIT 17. MILLBROOK BUSINESS PARK, SYBRON WAY
 CROWBOROUGH, EAST SUSSEX TN6 3JZ UNITED KINGDOM
 PHONE: 00 44 (0) 1892-665313, FAX: 00 44 (0) 1892-668838
 INTERNET: www.charleswater.co.uk

Drawing Number
60000.E

DATE:
05/01